

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A laser line beam emitting apparatus comprising:
a laser beam emitter for emitting a laser beam there from, the laser beam emitter having an optical broad element through which the emitted laser beam flux are vertically or horizontally broadened so that a vertical or horizontal straight line is formed and drawn on its objects, the broadened laser beam flux having a central optical axis,
a main covering for surrounding and covering said laser beam emitter therewith, the main covering comprising a plurality of faces and having at least one long length outlet formed on said faces which the vertically or horizontally broadened laser beam flux reach, and
a plurality of dust protective coverings consecutively provided in said outlet of the main covering for preventing entry of dust thereinto while allowing the passage therethrough of the broadened laser beam flux, the broadened laser beam flux being in part reflected from the interior of said dust protective covering to form a reflective laser beam, one of the dust protective coverings being arranged in a position through which said central optical axis of the broadened laser beam flux passes, the dust protective covering at the passage of the central optical axis of the broadened laser beam flux having a an interior curvature such that all of the reflected, emitted laser beam there from through the laser beam emitter is reflected into returns to the interior of the apparatus, and the reflected laser beam does not pass through said dust protective covering.
2. (Original) The laser line beam emitting apparatus of claim 1, wherein said dust protective covering has an inner surface on which said curve is formed with recess.
3. (Previously Amended) The laser line beam emitting apparatus of claim 1, wherein said dust protective covering with curvature comprises a ceiling of said main covering.

4. (Original) The laser line beam emitting apparatus of claim 1, wherein said dust protective covering with curvature is arranged at face served as a front of said main covering.

5. (Previously Amended) A laser line beam emitting apparatus comprising:
a main covering provided thereto, the main covering having at least a ceiling, a front, a back and sides;
a first outlet formed between said ceiling and the front nearer to said ceiling of the main covering,
a second outlet formed between said front and said sides of the main covering;
first and/or second laser beam emitting units provided in said main covering for emitting first and/or second laser beams there from, each of the first and second laser beam units having first and second emission elements in which respective cylindrical rod lenses are provided, the emitted laser beam having a central optical axis and beam flux, the beam flux of the emitted laser beams each being, after being collimated therein, broadened to two opposite directions approximately vertically or horizontally broadening from the central optical axes through one of the cylindrical rod lens, the first unit being disposed behind of said first outlet so that the vertically broadened laser beam is transmitted through the first outlet for formation of a vertical reference line drawn on its objects, the second unit being disposed behind of said second outlet so that the horizontally broadened laser beam is transmitted through the second outlet for formation of a horizontal reference line drawn on its objects; first and/or second dust protective covering members provided in said first and second outlets of the main covering, respectively and each having a reflecting surface formed on the inner surface thereof, the broadened, emitted laser beam flux from respective first and second units being in part reflected from the reflecting surface of the first and second dust protective covering members and in part passing therethrough; and

one or more curvatures formed on the reflecting surfaces of respective first and second dust protective covering members such that the parts of said reflected laser beam flux from the reflecting surfaces of respective first and second dust protective covering members return into the apparatus.

6. (Previously Amended) The laser line beam emitting apparatus of claim 5, wherein said first dust protective covering member comprises at least a pair of covering elements, the first covering element being arranged on the beam path on which the central optical axis and laser beam flux of the emissive laser beam from said first laser beam emitting unit run, the curvature of said first dust protective covering being formed from said first covering element, the second covering element being flat.

7. (Original) The laser line beam emitting apparatus of claim 6, wherein said second covering element of the first dust protective covering member also has a curvature formed on its internal surface.

8. (Previously Amended) The laser line beam emitting apparatus of claim 6, wherein said main covering has hold frames formed at a portion in which said first covering element of the first dust protective covering member is opposed to said second covering element of the first dust protective covering member at respective ends thereof, for holding thereon said first and second covering elements of the first dust protective covering.

9. (Previously Amended) The laser line beam emitting apparatus of claim 7, wherein said first and second covering elements of the first dust protective covering member are connected with each other at a portion where they are opposed to, and formed integrally with each other.

10. (Previously Amended) The laser line beam emitting apparatus of any of claims 6 to 9, wherein each of said cylindrical rod lenses of respective first and second laser beam emitting units has an outer surface with a curvature, and the curvatures of said first and/or second dust protective coverings members are formed in accordance with the curvatures of an external surfaces of respective cylindrical rod lenses, respectively.

11. (Original) The laser line beam emitting apparatus of claim 5, wherein each of said first and/or second dust protective coverings comprises three covering elements, the first covering element having a center portion arranged at an optical path through which the central optical axis of the broadened, emitted laser beam from the first or second laser beam emitting unit passes, and both edges, the second covering element extending from one of said edges to the interior of the apparatus, the third covering element extending from the other of said edges to the interior of the apparatus, said curvatures of the first and/or second dust protective coverings being formed on said first covering elements, respectively.

12. (Original) The laser line beam emitting apparatus of claim 11, wherein each of said cylindrical rod lenses of the first and/or second laser beam emitting units has an external surface with a curvature, and at least one of the curvatures of said first, second, and a third dust protective coverings is formed in accordance with respective ones of said cylindrical rod lenses of corresponding first and second laser beam emitters.

13. (Currently Amended) A dust protective covering provided in a laser line beam emitting apparatus having a housing; at least a laser beam emitter provided in said housing for emission and broadening of the laser beam flux to any directions in which objects to be emitted reside for draw of a straight reference line thereon, the objects being above, ahead and/or behind of or ahead, opposite sides and/or behind of the apparatus, the reference line being formed by the transverse section of said broadened, emitted laser beam flux; and an outlet provided on said housing for permitting escape of the

broadened, emitted laser beam there from, the dust protective covering being provided in said outlet so as to protect the apparatus from dust, said dust protective covering comprising an inner surface opposite to said laser beam emitter, an outer surface opposite to said objects, and a curvature formed on said inner surface thereof so that ~~said a~~ reflected, broadened laser beam flux therefrom ~~in part~~ wholly returns to the inside of the apparatus and does not pass through said dust protective covering.

14. (Previously Amended) The laser line beam emitting apparatus of claim 13, wherein said laser beam emitter has a cylindrical rod lens provided therein, wherein said cylindrical rod lenses of the laser beam emitter has an outer surface with curvature, and wherein said curvatures of the first and/or second dust protective coverings are formed in accordance with ones of said cylindrical rod lens.